

SKID STEERS

■ 2066 ■



mustangmfg.com

serious MUSCLE for serious work



- High-reaching radial-lift design reaches heights up to 122 inches with 12.00 tires or 120 inches with 10.00 tires.

- Rated operating capacity of 1,900 pounds, or 2,050 pounds with optional counterweight, make a powerful dent in your workload.
- Powered by a 68 HP Yanmar Tier III-certified turbocharged diesel engine, this machine provides extra power when needed.
- The tilt-back ROPS and large engine cover exposes internal components quickly for faster and easier maintenance and service.
- Excellent visibility to the rear tires and an open-front design provides better visibility to the front of the loader.

For more information on Mustang equipment, call our literature hotline at

800-628-0491

or visit our website:
mustangmfg.com



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs.
(79 kg) operator and full fuel tank

SPECIFICATIONS

	2066	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	162" (4115)
	B. Height to Hinge Pin - Fully Raised (mm)	123" (3124)
	C. Overall Height to Top of ROPS (mm)	81" (2057)
	D. Ground Clearance to Chassis (mm)	8.0" (203)
	E. Overall Length with Bucket (mm)	131" (3327)
	F. Overall Length without Bucket (mm)	99.5" (2527)
	G. Wheelbase (mm)	42.5" (1080)
	H. Dump Reach at Full Height (mm)	32" (813)
	I. Bucket Rollback at Ground	28°
	J. Dump Angle	37°
	K. Overall Width (mm)	69" (1753)
	L. Bucket Width (mm)	70" (1778)
	M. Clearance Circle - Rear (mm)	66" (1679)
	N. Clearance Circle - Front without Bucket (mm)	50.5" (1283)
	O. Clearance Circle - Front with Bucket (mm)	82" (2083)
	P. Seat to Ground Height (mm)	42" (1067)
	Q. Rollback at Full Height	84°
	R. Dump Height (mm)	93.5" (2375)
	S. Departure Angle	26°
	Standard Specification Tire Size	12.00x16.5 HD
ENGINE	Make	Yanmar
	Model	4TNV98-Tier III
	Power (kW) @ rpm	68 hp (51) @2500
	Displacement (L)	202 cu.in. (3.3)
	Maximum Torque (Nm) @ rpm	180 ft.-lbs (244) @ 1600
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	21.8 gpm (82.3)
	High-Flow Hydraulics - Optional (L/min)	36.9 gpm (139.6)
	Filtration	4 micron
	System Relief Pressure (bar)	3000 psi (207)
	Reservoir Capacity (L)	16 gal. (60)
CAPACITIES / WEIGHT	Rated Operating Capacity ^A (kg)	2000 lbs. (907)
	With Optional Counterweight ^A (kg)	2300 lbs. (1043)
	Tipping Load (kg)	4400 lbs. (1995)
	Fuel Tank (L)	19 gal. (71.9)
	Travel Speed - Maximum (km/hr)	12.3 mph (19.8)
	Operating Weight ^B - Approximate (kg)	7460 lbs. (3384)

